

					
	DuraScan® 700 Series	DuraScan® 800 Series	DuraSled 800 Series	SocketScan® 700 Series	SocketScan® 800 Series
Scanner Model	D760	D860	D560	S760	S860
Scanner Type	2D/1D Barcode Imager & OCR character reader	2D/1D Barcode Imager & OCR character reader	2D/1D Barcode Imager & OCR character reader	2D/1D Barcode Imager & OCR character reader	2D/1D Barcode Imager & OCR character reader
Height	1.6"	0.66	Varies depending on the size of the phone	1.6"	0.52"
Width	1.5"	2.37"		1.5"	2.12"
Length	5.2"	4.2"		5.2"	3.42"
Weight	3.8 oz	2.52 oz		4.1 oz	1.7 oz
Scan LED	Green & Red	Red & Green	Red & Green	Green & Red	Red & Green
Bluetooth LED	Blue	Blue	Blue	Blue	Blue
Battery LED	Green, Amber & Red	Red & Green	Red & Green	Green, Amber & Red	Red & Green
On screen scanning	Yes	Yes	Yes	Yes	Yes
Ambient Light	From 0 to 100 000 lux. From pitch black to direct sun light	From 0 to 100 000 lux. From pitch black to direct sun light	From 0 to 100 000 lux. From pitch black to direct sun light	From 0 to 100 000 lux. From pitch black to direct sun light	From 0 to 100 000 lux. From pitch black to direct sun light
Operating Temperature	+32 to +122°F (0 to +50°C)	+32 to +122°F (0 to +50°C)	+32 to +122°F (0 to +50°C)	+32 to +122°F (0 to +50°C)	+32 to +122°F (0 to +50°C)
Storage Temperature	-22 to +158°F (-30 to +70°C)	-22 to +158°F (-30 to +70°C)	-22 to +158°F (-30 to +70°C)	-22 to +158°F (-30 to +70°C)	-22 to +158°F (-30 to +70°C)
Relative Humidity	5% to 95% non-condensing	5% to 95% non-condensing	5% to 95% non-condensing	5% to 95% non-condensing	5% to 95% non-condensing
Sealing (Ingress Protection rating for dust and water)	IP54	IP40 (5% to 95% non-condensing)	IP40 (5% to 95% non-condensing)	IP40 (5% to 95% non-condensing)	IP40 (5% to 95% non-condensing)
Drop Specification	6 drops to concrete - 1 on each side at 6.6 ft. (2 m)	Multiple drops to vinyl covered concrete at 3 feet or 1 meter	Multiple drops to vinyl covered concrete at 3 feet or 1 meter	4 ft. to linoleum	Multiple 3.3 ft (1 m) drops to vinyl covered concrete
Tumble Specification	2,500 cycles at 3.3 ft. (1 m) to metal plate, IEC6008-2-31, IEC60069-2-32	N/A	N/A	N/A	N/A
Scan Angle	42° (Horizontal) - 28° (Vertical)	42° (Horizontal) - 28° (Vertical)	42° (Horizontal) - 28° (Vertical)	42° (Horizontal) - 28° (Vertical)	42° (Horizontal) - 28° (Vertical)
Optical Resolution	640 horizontal x 400 vertical pixels	640 horizontal x 400 vertical pixels	640 horizontal x 400 vertical pixels	640 horizontal x 400 vertical pixels	640 horizontal x 400 vertical pixels
Print Contrast	Down to 25%	Down to 25%	Down to 25%	Down to 25%	Down to 25%
Reading Distance	4.6 to 76.2 cm (1.8 to 30.0 in.) Depends on barcode size, symbology, label media, Narrow and Wide ratio, scan angle	4.6 to 76.2 cm (1.8 to 30.0 in.) Depends on barcode size, symbology, label media, Narrow and Wide ratio, scan angle	4.6 to 76.2 cm (1.8 to 30.0 in.) Depends on barcode size, symbology, label media, Narrow and Wide ratio, scan angle	4.6 to 76.2 cm (1.8 to 30.0 in.) Depends on barcode size, symbology, label media, Narrow and Wide ratio, scan angle	4.6 to 76.2 cm (1.8 to 30.0 in.) Depends on barcode size, symbology, label media, Narrow and Wide ratio, scan angle
Default 1D Symbologies	Codabar, Code 39, Code 93, Code 128, EAN-13/JAN, EAN-8/JAN, GS1 Databar, GS1 Databar Expanded, GS1 Databar Limited, GS1-128, Interleaved 2 of 5, ISBT 128, UPC A, UPC EO	Codabar, Code 39, Code 93, Code 128, EAN-13/JAN, EAN-8/JAN, GS1 Databar, GS1 Databar Expanded, GS1 Databar Limited, GS1-128, Interleaved 2 of 5, ISBT 128, UPC A, UPC EO	Codabar, Code 39, Code 93, Code 128, EAN-13/JAN, EAN-8/JAN, GS1 Databar, GS1 Databar Expanded, GS1 Databar Limited, GS1-128, Interleaved 2 of 5, ISBT 128, UPC A, UPC EO	Codabar, Code 39, Code 93, Code 128, EAN-13/JAN, EAN-8/JAN, GS1 Databar, GS1 Databar Expanded, GS1 Databar Limited, GS1-128, Interleaved 2 of 5, ISBT 128, UPC A, UPC EO	Codabar, Code 39, Code 93, Code 128, EAN-13/JAN, EAN-8/JAN, GS1 Databar, GS1 Databar Expanded, GS1 Databar Limited, GS1-128, Interleaved 2 of 5, ISBT 128, UPC A, UPC EO
Default 2D Symbologies	Aztec, Data Matrix, Maxicode, Micro PDF417, PDF417, DotCode/Postal Codes: Australia Post	Aztec, Data Matrix, Maxicode, Micro PDF417, PDF417, DotCode/Postal Codes: Australia Post	Aztec, Data Matrix, Maxicode, Micro PDF417, PDF417, DotCode/Postal Codes: Australia Post	Aztec, Data Matrix, Maxicode, Micro PDF417, PDF417, DotCode/Postal Codes: Australia Post	Aztec, Data Matrix, Maxicode, Micro PDF417, PDF417, DotCode/Postal Codes: Australia Post
Default OCR Type Face	OCR Passport - 2 lines	OCR Passport - 2 lines	OCR Passport - 2 lines	OCR Passport - 2 lines	OCR Passport - 2 lines
Supported 1D Symbologies:	Bookland EAN, Chinese 2 of 5, Codabar, Code 11, Code 39, Code 93, Code 128, Composite CC-A/B, Composite CC-C, Composite TLC, Discrete 2 of 5, EAN-13/JAN, EAN-8/JAN, GS1 Databar, GS1 Databar Expanded, GS1 Databar Limited, GS1-128, Interleaved 2 of 5, ISBT 128, ISSN EAN, Matrix 2 of 5, MSI, UPC/EAN/JAN, UPC A, UPC EO	Bookland EAN, Chinese 2 of 5, Codabar, Code 11, Code 39, Code 93, Code 128, Composite CC-A/B, Composite CC-C, Composite TLC, Discrete 2 of 5, EAN-13/JAN, EAN-8/JAN, GS1 Databar, GS1 Databar Expanded, GS1 Databar Limited, GS1-128, Interleaved 2 of 5, ISBT 128, ISSN EAN, Matrix 2 of 5, MSI, UPC/EAN/JAN, UPC A, UPC EO	Bookland EAN, Chinese 2 of 5, Codabar, Code 11, Code 39, Code 93, Code 128, Composite CC-A/B, Composite CC-C, Composite TLC, Discrete 2 of 5, EAN-13/JAN, EAN-8/JAN, GS1 Databar, GS1 Databar Expanded, GS1 Databar Limited, GS1-128, Interleaved 2 of 5, ISBT 128, ISSN EAN, Matrix 2 of 5, MSI, UPC/EAN/JAN, UPC A, UPC EO	Bookland EAN, Chinese 2 of 5, Codabar, Code 11, Code 39, Code 93, Code 128, Composite CC-A/B, Composite CC-C, Composite TLC, Discrete 2 of 5, EAN-13/JAN, EAN-8/JAN, GS1 Databar, GS1 Databar Expanded, GS1 Databar Limited, GS1-128, Interleaved 2 of 5, ISBT 128, ISSN EAN, Matrix 2 of 5, MSI, UPC/EAN/JAN, UPC A, UPC EO	Bookland EAN, Chinese 2 of 5, Codabar, Code 11, Code 39, Code 93, Code 128, Composite CC-A/B, Composite CC-C, Composite TLC, Discrete 2 of 5, EAN-13/JAN, EAN-8/JAN, GS1 Databar, GS1 Databar Expanded, GS1 Databar Limited, GS1-128, Interleaved 2 of 5, ISBT 128, ISSN EAN, Matrix 2 of 5, MSI, UPC/EAN/JAN, UPC A, UPC EO
Supported 2D Symbologies:	Aztec, Data Matrix, Dot Code, Han Xin, Maxicode, Micro PDF417, MicroQR, PDF417, QR Code, DotCode/Postal Codes: Australia Post, Japan Postal, KIX Code, Maxicode, Netherlands, UPU FICS Posta, US Planet, US Postnet, USPS 4CB/One Code/Intelligent Mail number	Aztec, Data Matrix, Dot Code, Han Xin, Maxicode, Micro PDF417, MicroQR, PDF417, QR Code, DotCode/Postal Codes: Australia Post, Japan Postal, KIX Code, Maxicode, Netherlands, UPU FICS Posta, US Planet, US Postnet, USPS 4CB/One Code/Intelligent Mail	Aztec, Data Matrix, Dot Code, Han Xin, Maxicode, Micro PDF417, MicroQR, PDF417, QR Code, DotCode/Postal Codes: Australia Post, Japan Postal, KIX Code, Maxicode, Netherlands, UPU FICS Posta, US Planet, US Postnet, USPS 4CB/One Code/Intelligent Mail	Aztec, Data Matrix, Dot Code, Han Xin, Maxicode, Micro PDF417, MicroQR, PDF417, QR Code, DotCode/Postal Codes: Australia Post, Japan Postal, KIX Code, Maxicode, Netherlands, UPU FICS Posta, US Planet, US Postnet, USPS 4CB/One Code/Intelligent Mail	Aztec, Data Matrix, Dot Code, Han Xin, Maxicode, Micro PDF417, MicroQR, PDF417, QR Code, DotCode/Postal Codes: Australia Post, Japan Postal, KIX Code, Maxicode, Netherlands, UPU FICS Posta, US Planet, US Postnet, USPS 4CB/One Code/Intelligent Mail
Supported OCR Type Face	OCR-A, OCR-B, MICR-E13B, US currency serial number	OCR-A, OCR-B, MICR-E13B, US currency serial number	OCR-A, OCR-B, MICR-E13B, US currency serial number	OCR-A, OCR-B, MICR-E13B, US currency serial number	OCR-A, OCR-B, MICR-E13B, US currency serial number
Battery Type	1400 mAh Lithium - Ion Battery			2 rechargeable, 2000 mAh (LR6) NiMH (replaceable battery)	700 mAh Lithium ion rechargeable battery
Charge Time	6 Hours			6 Hours	4 Hours
Standby Time	20 Hours			20 Hours	25 hours
Active Scan Time	85,000 scans within 9 hours (based on 2 scans every 1 second) or 17,000 scans within 19 hours (based on 1 scan every 4 seconds)	34,000 scans within 3 hours (based on 2 scans every 1 second) or 9,000 scans within 10 hours (based on 1 scan every 4 seconds)	34,000 scans within 3 hours (based on 2 scans every 1 second) or 9,000 scans within 10 hours (based on 1 scan every 4 seconds)	70,000 scans within 9 hours (based on 2 scans every 1 second) or 17,000 scans within 19 hours (based on 1 scan every 4 seconds)	34,000 scans within 3 hours (based on 2 scans every 1 second) or 9,000 scans within 10 hours (based on 1 scan every 4 seconds)
Bluetooth Radio	Class 1 Bluetooth, version 2.1 + EDR (Enhanced Data Rates) with 56-bit data encryption	Class 2 Bluetooth, version 2.1 + EDR (Enhanced Data Rates) with 56-bit data encryption	Class 2 Bluetooth, version 2.1 + EDR (Enhanced Data Rates) with 56-bit data encryption	Class 2 Bluetooth, version 2.1 + EDR (Enhanced Data Rates) with 56-bit data encryption	Class 2 Bluetooth, version 2.1 + EDR (Enhanced Data Rates) with 56-bit data encryption
Bluetooth Range	Up to 100 m (330 ft.)	Up to 10 m (33 ft)	Up to 10 m (33 ft)	Up to 10 m (33 ft)	Up to 10 m (33 ft)
Bluetooth Profiles: Basic Mode	Human Interface Device (HID)*, Application Mode - Serial Port Profile (SPP) and Application	Human Interface Device (HID)*, Application Mode - Serial Port Profile (SPP) and Application	Human Interface Device (HID)*, Application Mode - Serial Port Profile (SPP) and Application	Human Interface Device (HID)*, Application Mode - Serial Port Profile (SPP) and Application	Human Interface Device (HID)*, Application Mode - Serial Port Profile (SPP) and Application
Bluetooth Profiles: MFI-SPP Mode	*By default, the scanner is set to Basic Mode (HID).	Some Operating Systems or smartphone/tablet models may support only one profile.	Some Operating Systems or smartphone/tablet models may support only one profile.	Some Operating Systems or smartphone/tablet models may support only one profile.	Some Operating Systems or smartphone/tablet models may support only one profile.
Bluetooth SIG	Declaration ID: D030473 QD ID: 82009	Declaration ID: D030473 QD ID: 82009	Declaration ID: D030473 QD ID: 82009	Declaration ID: D030473 QD ID: 82009	Declaration ID: D030473 QD ID: 82009
Electrical Safety	Certified to IEC 60950-1, UL 60950-1, CAN/CSA C22.2	Certified to IEC 60950-1, UL 60950-1, CAN/CSA C22.2	Certified to IEC 60950-1, UL 60950-1, CAN/CSA C22.2	Certified to IEC 60950-1, UL 60950-1, CAN/CSA C22.2	Certified to IEC 60950-1, UL 60950-1, CAN/CSA C22.2
Environmental	RoHS EN 50581	RoHS EN 50581	RoHS EN 50581	RoHS EN 50581	RoHS EN 50581
EM/RFI	FCC Part 15 Class C, RSS 210, iCES 003, C-Tick, CISPR 22, CE EN55022, EN55024, TELEC FCC ID: T9J-RN41-3 IC: 6514A-RN413 Telec ID: R 201-135280	FCC Part 15 Class C, RSS 210, iCES 003, C-Tick, CISPR 22, CE EN55022, EN55024, TELEC FCC ID: T9J-RN42 IC: 6514A-RN42 Telec ID: 201-125709	FCC Part 15 Class C, RSS 210, iCES 003, C-Tick, CISPR 22, CE EN55022, EN55024, TELEC FCC ID: T9J-RN42 IC: 6514A-RN42 Telec ID: 201-125709	FCC Part 15 Class C, RSS 210, iCES 003, C-Tick, CISPR 22, CE EN55022, EN55024, TELEC FCC ID: LUBM44 IC ID: 2529A-MA4157 Telec: R 211-181219	FCC Part 15 Class C, RSS 210, iCES 003, C-Tick, CISPR 22, CE EN55022, EN55024, TELEC FCC ID: T9J-RN42 IC: 6514A-RN42 Telec ID: 201-125709
LED Safety	IEC 62471, EN 62471 (EXEMPT GROUP)	IEC 62471, EN 62471 (EXEMPT GROUP)	IEC 62471, EN 62471 (EXEMPT GROUP)	IEC/EN 62471 (EXEMPT GROUP)	IEC 60825-1, EN 60825-1
Warranty	Standard one year limited warranty	Standard one year limited warranty	Standard one year limited warranty	Standard one year limited warranty	Standard one year limited warranty
Extended Warranty	Sold separately	Sold separately	Sold separately	Sold separately	Sold separately
User Replacement Battery	Field Replaceable battery available	The unit needs to be sent in to Socket for service. Please submit an online ticket and request for Return Merchandise Authorization(RMA).	The unit needs to be sent in to Socket for service. Please submit an online ticket and request for Return Merchandise Authorization(RMA).	2 rechargeable, 2000 mAh (LR6) NiMH (replaceable battery)	The unit needs to be sent in to Socket for service. Please submit an online ticket and request for Return Merchandise Authorization(RMA).
How to Buy:	Worldwide Europe Japan Australia United Kingdom	Worldwide Europe Japan Australia United Kingdom	Worldwide Europe Japan Australia United Kingdom	Worldwide Europe Japan Australia United Kingdom	Worldwide Europe Japan Australia United Kingdom
(MSRP) List Price:	\$569	\$529	\$546	\$479	\$479